

## (12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
8 July 2004 (08.07.2004)

PCT

(10) International Publication Number  
**WO 2004/057746 A1**

(51) International Patent Classification<sup>7</sup>: **H02M 7/00**

(21) International Application Number:  
PCT/SE2003/002073

(22) International Filing Date:  
22 December 2003 (22.12.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
0203835-4 23 December 2002 (23.12.2002) SE

(71) Applicant (for all designated States except US):  
**DANAHER MOTION STOCKHOLM AB** [SE/SE];  
Solkraftsvägen 13, S-135 70 Stockholm (SE).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **ANDERSSON,**  
**Tord, Rickard** [SE/SE]; Borgvägen 11, S-135 55 Tyresö

(SE). **FÖRBORGEN, Carl, Mikael** [SE/SE]; Fårtick-  
evägen 19, S-135 33 Tyresö (SE). **GALLAS, Oliver**  
[SE/SE]; Karlsborgsvägen 13, S-121 50 Johanneshov  
(SE). **KARLSSON, Ulf, Ingemar** [SE/SE]; Sikvägen 23,  
6tr, S-135 41 Tyresö (SE). **MALMSTRÖM, Carl-Erik**  
[SE/SE]; Lindalsvägen 55 A, S-135 50 Tyresö (SE).

(74) Agent: **PANTZAR, Tord**; c/o Atlas Copco Tools AB,  
S-105 23 Stockholm (SE).

(81) Designated States (national): JP, US.


(84) Designated States (regional): European patent (AT, BE,  
BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU,  
IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guid-  
ance Notes on Codes and Abbreviations" appearing at the begin-  
ning of each regular issue of the PCT Gazette.

(54) Title: INVERTER TYPE MOTOR DRIVE UNIT



(57) Abstract: An inverter type drive unit for feeding AC electric power of variable parameters to an electric motor comprises an electronic control section (40), a power converting and an output section comprising one or more identical power modules (11a-c), each forming a complete 3-phase output stage and arranged in a side-by-side disposition in a multiplying direction (A) and clamped by means of retaining devices (14a-c) to a cooling structure (10), wherein the power modules (11a-c) are connected in parallel to DC input terminals (25, 26) and to AC output terminals (32, 33, 34) via conductive sheets (20, 21, 27a-c), whereof the DC connected sheets (20, 21) cover substantially the entire physical surface area covered by the power modules (11a-c) so as to accomplish an even, simultaneous and low impedance DC current supply to all power modules (11a-c).